


OpenGL Compute Shaders


Mike Bailey

mjb@cs.oregonstate.edu

Oregon State University




compute.shader.pptx



mjb – January 1, 2019

OpenGL Compute Shader – the Basic Idea



Paraphrased from the `ARB_compute_shader` spec:

Recent graphics hardware has become extremely powerful. A strong desire to harness this power for work that does not fit the traditional graphics pipeline has emerged. To address this, Compute Shaders are a new single-stage program. They are launched in a manner that is essentially stateless. This allows arbitrary workloads to be sent to the graphics hardware with minimal disturbance to the GL state machine.

In most respects, a Compute Shader is identical to all other OpenGL shaders, with similar status, uniforms, and other such properties. It has access to many of the same data as all other shader types, such as textures, image textures, atomic counters, and so on. However, the Compute Shader has no predefined inputs, nor any fixed-function outputs. It cannot be part of a rendering pipeline and its visible side effects are through its actions on shader storage buffers, image textures, and atomic counters.

Why Not Just Use OpenCL Instead?

OpenCL is *great!* It does a super job of using the GPU for general-purpose data-parallel computing. And, OpenCL is more feature-rich than OpenGL compute shaders. So, why use Compute Shaders *ever* if you've got OpenCL? Here's what I think:

- OpenCL requires installing a separate driver and separate libraries. While this is not a huge deal, it does take time and effort. When everyone catches up to OpenGL 4.3, Compute Shaders will just “be there” as part of core OpenGL.
- Compute Shaders use the GLSL language, something that all OpenGL programmers should already be familiar with (or will be soon).
- Compute shaders use the same context as does the OpenGL rendering pipeline. There is no need to acquire and release the context as OpenGL+OpenCL must do.
- I'm assuming that calls to OpenGL compute shaders are more lightweight than calls to OpenCL kernels are. (true?) This should result in better performance. (true? how much?)
- Using OpenCL is somewhat cumbersome. It requires a lot of setup (queries, platforms, devices, queues, kernels, etc.). Compute Shaders look to be more convenient. They just kind of flow in with the graphics.


The bottom line is that I will continue to use OpenCL for the big, bad stuff. But, for lighter-weight data-parallel computing that interacts with graphics, I will use the Compute Shaders.

I suspect that a good example of a lighter-weight data-parallel graphics-related application is a **particle system**. This will be shown here in the rest of these notes. I hope I'm right.

If I Know GLSL, What Do I Need to Do Differently to Write a Compute Shader?

Not much:

1. A Compute Shader is created just like any other GLSL shader, except that its type is `GL_COMPUTE_SHADER` (duh...). You compile it and link it just like any other GLSL shader program.
2. A Compute Shader must be in a shader program all by itself. There cannot be vertex, fragment, etc. shaders in there with it. (why?)
3. A Compute Shader has access to uniform variables and buffer objects, but cannot access any pipeline variables such as attributes or variables from other stages. It stands alone.
4. A Compute Shader needs to declare the number of work-items in each of its work-groups in a special GLSL *layout* statement.




More information on items 3 and 4 are coming up . . .

Passing Data to the Compute Shader Happens with a Cool New Buffer Type – the *Shader Storage Buffer Object*

The tricky part is getting data into and out of the Compute Shader. The trickiness comes from the specification phrase: “In most respects, a Compute Shader is identical to all other OpenGL shaders, with similar status, uniforms, and other such properties. It has access to many of the same data as all other shader types, such as textures, image textures, atomic counters, and so on.”


OpenCL programs have access to general arrays of data, and also access to OpenGL arrays of data in the form of buffer objects. Compute Shaders, looking like other shaders, haven’t had *direct* access to general arrays of data (hacked access, yes; direct access, no). But, because Compute Shaders represent opportunities for massive data-parallel computations, that is exactly what you want them to use.

Thus, OpenGL 4.3 introduced the **Shader Storage Buffer Object**. This is very cool, and has been needed for a long time!




Shader Storage Buffer Objects are created with arbitrary data (same as other buffer objects), but what is new is that the shaders can read and write them in the same C-like way as they were created, including treating parts of the buffer as an array of structures – perfect for data-parallel computing!

Passing Data to the Compute Shader Happens with a Cool New Buffer Type – the *Shader Storage Buffer Object*




And, like other OpenGL buffer types, Shader Storage Buffer Objects can be bound to indexed binding points, making them easy to access from inside the Compute Shaders.



(Any resemblance this diagram has to a mother sow is accidental, but not entirely inaccurate...)

The Example We Are Going to Use Here is a *Particle System*



Setting up the Shader Storage Buffer Objects in Your C Program

```
#define NUM_PARTICLES      1024*1024      // total number of particles to move
#define WORK_GROUP_SIZE   128            // # work-items per work-group

struct pos
{
    float x, y, z, w;      // positions
};

struct vel
{
    float vx, vy, vz, vw; // velocities
};

struct color
{
    float r, g, b, a;      // colors
};

// need to do the following for both position, velocity, and colors of the particles:

GLuint posSSbo;
GLuint velSSbo;
GLuint colSSbo;
```

Note that `.w` and `.vw` are not actually needed. But, by making these structure sizes a multiple of 4 floats, it doesn't matter if they are declared with the `std140` or the `std430` qualifier. I think this is a good thing.

Setting up the Shader Storage Buffer Objects in Your C Program


```
glGenBuffers( 1, &posSSbo);
glBindBuffer( GL_SHADER_STORAGE_BUFFER, posSSbo );
glBufferData( GL_SHADER_STORAGE_BUFFER, NUM_PARTICLES * sizeof(struct pos), NULL, GL_STATIC_DRAW );

GLint bufMask = GL_MAP_WRITE_BIT | GL_MAP_INVALIDATE_BUFFER_BIT ;           // the invalidate makes a big difference when re-writing


struct pos *points = (struct pos *) glMapBufferRange( GL_SHADER_STORAGE_BUFFER, 0, NUM_PARTICLES * sizeof(struct pos), bufMask );
for( int i = 0; i < NUM_PARTICLES; i++ )
{
    points[ i ].x = Ranf( XMIN, XMAX );
    points[ i ].y = Ranf( YMIN, YMAX );
    points[ i ].z = Ranf( ZMIN, ZMAX );
    points[ i ].w = 1.;
}
glUnmapBuffer( GL_SHADER_STORAGE_BUFFER );

glGenBuffers( 1, &velSSbo);
glBindBuffer( GL_SHADER_STORAGE_BUFFER, velSSbo );
glBufferData( GL_SHADER_STORAGE_BUFFER, NUM_PARTICLES * sizeof(struct vel), NULL, GL_STATIC_DRAW );

struct vel *vels = (struct vel *) glMapBufferRange( GL_SHADER_STORAGE_BUFFER, 0, NUM_PARTICLES * sizeof(struct vel), bufMask );
for( int i = 0; i < NUM_PARTICLES; i++ )
{
    vels[ i ].vx = Ranf( VXMIN, VXMAX );
    vels[ i ].vy = Ranf( VYMIN, VYMAX );
    vels[ i ].vz = Ranf( VZMIN, VZMAX );
    vels[ i ].vw = 0.;
}
glUnmapBuffer( GL_SHADER_STORAGE_BUFFER );
```




The diagram shows a yellow box labeled "Shader Storage Buffer Object" with an arrow pointing down to a vertical stack of four yellow rectangular blocks, representing the memory layout for the position data.




The diagram shows a yellow box labeled "Shader Storage Buffer Object" with an arrow pointing down to a vertical stack of four yellow rectangular blocks, representing the memory layout for the velocity data.

The Data Needs to be Divided into Large Quantities call *Work-Groups*, each of¹¹ which is further Divided into Smaller Units Called *Work-Items*

20 total items to compute:



The Invocation Space can be 1D, 2D, or 3D. This one is 1D.




$$\#WorkGroups = \frac{GlobalInvocationSize}{WorkGroupSize}$$

$$5 \times 4 = \frac{20}{4}$$

The Data Needs to be Divided into Large Quantities call Work-Groups, each of 12 which is further Divided into Smaller Units Called Work-Items


20x12 (=240) total items to compute:




The Invocation Space can be 1D, 2D, or 3D. This one is 2D.

$$\#WorkGroups = \frac{GlobalInvocationSize}{WorkGroupSize}$$

$$5 \times 4 = \frac{20 \times 12}{4 \times 3}$$




```
void glDispatchCompute( num_groups_x, num_groups_y, num_groups_z );
```



If the problem is 2D, then
 $\text{num_groups_z} = 1$

If the problem is 1D, then
 $\text{num_groups_y} = 1$ and
 $\text{num_groups_z} = 1$

A Mechanical Equivalent...



“Streaming Multiprocessor”

“CUDA Cores”

“Data”



Invoking the Compute Shader in Your C Program



```
glBindBufferBase( GL_SHADER_STORAGE_BUFFER, 4, posSSbo );
glBindBufferBase( GL_SHADER_STORAGE_BUFFER, 5, velSSbo );
glBindBufferBase( GL_SHADER_STORAGE_BUFFER, 6, colSSbo );

...

glUseProgram( MyComputeShaderProgram );
glDispatchCompute( NUM_PARTICLES / WORK_GROUP_SIZE, 1, 1 );
glMemoryBarrier( GL_SHADER_STORAGE_BARRIER_BIT );

...

glUseProgram( MyRenderingShaderProgram );
glBindBuffer( GL_ARRAY_BUFFER, posSSbo );
glVertexPointer( 4, GL_FLOAT, 0, (void *)0 );
glEnableClientState( GL_VERTEX_ARRAY );
glDrawArrays( GL_POINTS, 0, NUM_PARTICLES );
glDisableClientState( GL_VERTEX_ARRAY );
glBindBuffer( GL_ARRAY_BUFFER, 0 );
```



Writing a C++ Class to Handle Everything is Fairly Straightforward

Setup:

```
GLSLProgram *Particles = new GLSLProgram( );  
bool valid = Particles->Create( "particles.cs" );  
if( ! valid ) { . . . }
```

Using:

```
Particles->Use( );  
Particles->DispatchCompute( NUM_PARTICLES / WORK_GROUP_SIZE, 1, 1 );  
  
Render->Use( );  
. . .
```


Special Pre-set Variables in the Compute Shader

in	uvec3	gl_NumWorkGroups ;	Same numbers as in the <i>glDispatchCompute</i> call
const	uvec3	gl_WorkGroupSize ;	Same numbers as in the <i>layout local_size_*</i>
in	uvec3	gl_WorkGroupID ;	Which workgroup this thread is in
in	uvec3	gl_LocalInvocationID ;	Where this thread is in the current workgroup
in	uvec3	gl_GlobalInvocationID ;	Where this thread is in <i>all</i> the work items
in	uint	gl_LocalInvocationIndex ;	1D representation of the <i>gl_LocalInvocationID</i> (used for indexing into a shared array)

$$0 \leq \text{gl_WorkGroupID} \leq \text{gl_NumWorkGroups} - 1$$

$$0 \leq \text{gl_LocalInvocationID} \leq \text{gl_WorkGroupSize} - 1$$

$$\text{gl_GlobalInvocationID} = \text{gl_WorkGroupID} * \text{gl_WorkGroupSize} + \text{gl_LocalInvocationID}$$

$$\begin{aligned} \text{gl_LocalInvocationIndex} = & \text{gl_LocalInvocationID.z} * \text{gl_WorkGroupSize.y} * \text{gl_WorkGroupSize.x} + \\ & \text{gl_LocalInvocationID.y} * \text{gl_WorkGroupSize.x} + \\ & \text{gl_LocalInvocationID.x} \end{aligned}$$

The Particle System Compute Shader -- Setup

```
#version 430 compatibility
#extension GL_ARB_compute_shader : enable
#extension GL_ARB_shader_storage_buffer_object : enable;


layout( std140, binding=4 ) buffer Pos
{
    vec4 Positions[ ]; // array of structures
};

layout( std140, binding=5 ) buffer Vel
{
    vec4 Velocities[ ]; // array of structures
};

layout( std140, binding=6 ) buffer Col
{
    vec4 Colors[ ]; // array of structures
};

layout( local_size_x = 128, local_size_y = 1, local_size_z = 1 ) in;
```

You can use the empty brackets, but only on the *last* element of the buffer. The actual dimension will be determined for you when OpenGL examines the size of this buffer's data store.



The Particle System Compute Shader – The Physics

```
const vec3 G    = vec3( 0., -9.8, 0. );  
const float DT  = 0.1;
```


...

```
uint gid = gl_GlobalInvocationID.x;           // the .y and .z are both 1 in this case
```

```
vec3 p = Positions[ gid ].xyz;  
vec3 v = Velocities[ gid ].xyz;
```

```
vec3 pp = p + v*DT + .5*DT*DT*G;  
vec3 vp = v + G*DT;
```

```
Positions[ gid ].xyz = pp;  
Velocities[ gid ].xyz = vp;
```



$$p' = p + v \cdot t + \frac{1}{2} G \cdot t^2$$

$$v' = v + G \cdot t$$

The Particle System Compute Shader – How About Introducing a Bounce?

```


const vec4 Sphere = vec4( -100., -800., 0., 600. ); // x, y, z, r
                                                    // (could also have passed this in)

vec3
Bounce( vec3 vin, vec3 n )
{
    vec3 vout = reflect( vin, n );
    return vout;
}

vec3
BounceSphere( vec3 p, vec3 v, vec4 s )
{
    vec3 n = normalize( p - s.xyz );
    return Bounce( v, n );
}

bool
IsInsideSphere( vec3 p, vec4 s )
{
    float r = length( p - s.xyz );
    return ( r < s.w );
}

```



The Particle System Compute Shader – How About Introducing a Bounce?

```
uint gid = gl_GlobalInvocationID.x;           // the .y and .z are both 1 in this case
```

```
vec3 p = Positions[ gid ].xyz;
vec3 v = Velocities[ gid ].xyz;
```

```
vec3 pp = p + v*DT + .5*DT*DT*G;
vec3 vp = v + G*DT;
```

```
if( IsInsideSphere( pp, Sphere ) )
{
    vp = BounceSphere( p, v, Sphere );
    pp = p + vp*DT + .5*DT*DT*G;
}
```


```
Positions[ gid ].xyz = pp;
Velocities[ gid ].xyz = vp;
```

$$p' = p + v \cdot t + \frac{1}{2} G \cdot t^2$$

$$v' = v + G \cdot t$$

Graphics Trick Alert: Making the bounce happen from the surface of the sphere is time-consuming. Instead, bounce from the previous position in space. If DT is small enough, nobody will ever know...

The Bouncing Particle System Compute Shader – What Does It Look Like?



Other Useful Stuff – Copying Global Data to a Local Array Shared by the Entire Work-Group

There are some applications, such as image convolution, where threads within a work-group need to operate on each other's input or output data. In those cases, it is usually a good idea to create a local shared array that all of the threads in the work-group can access. You do it like this:

```
layout( std140, binding=6 ) buffer Col
{
    vec4 Colors[ ];
};

layout( shared ) vec4 rgba[ gl_WorkGroupSize.x ];

uint gid = gl_GlobalInvocationID.x;
uint lid = gl_LocalInvocationID.x;

rgba[ lid ] = Colors[ gid ];

memory_barrier_shared( );

    << operate on the rgba array elements >>

Colors[ gid ] = rgba[ lid ];
```